

CS 320

Computer Language Processing

Exercise Set 5

April 02, 2025

Consider a type system for a simple functional language, consisting of integers, booleans, parametric pairs, and lists. The rest of the exercises will revolve around this system.

$$\begin{array}{c}
\frac{(x, \tau) \in \Gamma}{\Gamma \vdash x : \tau} \text{ (var)} \\
\frac{n \text{ is an integer value}}{\Gamma \vdash \mathbf{num}(n) : \mathbf{int}} \text{ (int)} \\
\frac{e_1 : \mathbf{int} \quad e_2 : \mathbf{int}}{\Gamma \vdash e_1 + e_2 : \mathbf{int}} (+) \quad \frac{e_1 : \mathbf{int} \quad e_2 : \mathbf{int}}{\Gamma \vdash e_1 - e_2 : \mathbf{int}} (-) \\
\frac{b \text{ is a boolean value}}{\Gamma \vdash \mathbf{bool}(b) : \mathbf{bool}} \text{ (bool)} \\
\frac{\Gamma \vdash e_1 : \mathbf{bool} \quad \Gamma \vdash e_2 : \mathbf{bool}}{\Gamma \vdash e_1 \wedge e_2 : \mathbf{bool}} \text{ (and)} \quad \frac{\Gamma \vdash e_1 : \mathbf{bool} \quad \Gamma \vdash e_2 : \mathbf{bool}}{\Gamma \vdash e_1 \vee e_2 : \mathbf{bool}} \text{ (or)} \\
\frac{\Gamma \vdash e_1 : \mathbf{bool}}{\Gamma \vdash \neg e_1 : \mathbf{bool}} \text{ (not)} \\
\frac{\Gamma \vdash e_1 : \mathbf{bool} \quad \Gamma \vdash e_2 : \tau \quad \Gamma \vdash e_3 : \tau}{\Gamma \vdash \mathbf{if } e_1 \mathbf{ then } e_2 \mathbf{ else } e_3 : \tau} \text{ (ite)} \\
\frac{\Gamma \vdash e_1 : \tau_1 \quad \Gamma \vdash e_2 : \tau_2}{\Gamma \vdash (e_1, e_2) : (\tau_1, \tau_2)} \text{ (pair)} \\
\frac{\Gamma \vdash e : (\tau_1, \tau_2)}{\Gamma \vdash \mathbf{fst}(e) : \tau_1} \text{ (fst)} \quad \frac{\Gamma \vdash e : (\tau_1, \tau_2)}{\Gamma \vdash \mathbf{snd}(e) : \tau_2} \text{ (snd)} \\
\frac{}{\Gamma \vdash \mathbf{Nil}() : \mathbf{List}[\tau]} \text{ (nil)} \quad \frac{\Gamma \vdash e_1 : \tau \quad \Gamma \vdash e_2 : \mathbf{List}[\tau]}{\Gamma \vdash \mathbf{Cons}(e_1, e_2) : \mathbf{List}[\tau]} \text{ (cons)} \\
\frac{\Gamma, x : \tau_1 \vdash e : \tau_2}{\Gamma \vdash \lambda x : \tau_1 \Rightarrow e : \tau_1 \Rightarrow \tau_2} \text{ (fun)} \quad \frac{\Gamma \vdash e_1 : \tau_1 \Rightarrow \tau_2 \quad \Gamma \vdash e_2 : \tau_1}{\Gamma \vdash e_1 e_2 : \tau_2} \text{ (app)}
\end{array}$$

Exercise 1 For each of the following term-type pairs (t, τ) , check whether the term can be ascribed with the given type, i.e., whether there exists a derivation of $\Gamma \vdash t : \tau$ for some typing context Γ in the given system. If not, briefly argue why.

1. x, bool
2. $x + 1, \text{int}$
3. $(x \ \&\& \ y) == (x \leq 0), \text{bool}$
4. $f \Rightarrow x \Rightarrow y \Rightarrow f((x, y)):$
 $((\text{List}[\text{Int}], \text{Bool}) \Rightarrow \text{Int}) \Rightarrow \text{List}[\text{Int}] \Rightarrow \text{Bool} \Rightarrow \text{Int}$
5. $\text{Cons}(x, x) : \text{List}[\text{List}[\text{Int}]]$

Solution

1. x, Bool . Derivation, assume x is a boolean:

$$\frac{(x, \text{bool}) \in \{(x, \text{bool})\}}{\{(x, \text{bool})\} \vdash x : \text{Bool}}$$

Note that this would work with any type, as there are no constraints.

2. $x + 1, \text{int}$. Derivation, assume x is an integer:

$$\frac{\frac{(x, \text{int}) \in \{(x, \text{int})\}}{\{(x, \text{int})\} \vdash x : \text{Int}} \quad \frac{1 \in \mathbb{N}}{\{(x, \text{int})\} \vdash 1 : \text{Int}}}{\{(x, \text{int})\} \vdash x + 1 : \text{Int}}$$

Due to addition constraining the type of x , other possible types would not work.

3. $(x \ \&\& \ y) == (x \leq 0), \text{bool}$. Not well-typed. From the left-hand side, we would enforce that $x : \text{Bool}$, but on the right, we find $x : \text{Int}$. Due to this conflict, there is no valid derivation for this term.
4. $f \Rightarrow x \Rightarrow y \Rightarrow f((x, y))$: this is the currying function. Note that it will conform to $((a, b) \Rightarrow c) \Rightarrow a \Rightarrow b \Rightarrow c$ for any choice of a, b , and c . (check)
5. $\text{Cons}(x, x) : \text{List}[\text{List}[\text{Int}]]$. Not well-typed. The *cons* rule tells us that the second argument must have the same type as the result, so $x : \text{List}[\text{List}[\text{Int}]]$, but the first argument enforces the type to be $\text{List}[\text{Int}]$ (again, due to result type). As $\text{int} \neq \text{List}[\text{int}]$, this is not well-typed.

Note that the singular assignment of x to $\text{Nil}()$ can make a well typed term here, but the typing must hold for *all* possible values of x .

□

Exercise 2 A *program* is a top-level expression t accompanied by a set of user-provided function definitions. The program is well-typed if each of the function bodies conform to the type of the function, and the top-level expression is well-typed in the context of the function definitions.

For each of the following function definitions, check whether the function body is well-typed:

1. `def f(x:Int, y:Int):Bool = x <= y`
2. `def rec(x:Int):Int = rec(x)`
3. `def fib(n:Int):Int = if n <= 1 then 1 else (fib(n - 1) + fib(n - 2))`

Solution

1. Well-typed, apply rule *Leq*.
2. Well-typed. We need to check if the body conforms to the output type, if we know the function and its parameters have their ascribed type. So, under the context `rec: Int => Int, x: Int`, we need to prove that `rec(x): Int`. This follows from the *app* rule.

So, if we allow recursion and do not check for termination, we can prove unexpected things using the non-terminating programs.

3. Well-typed. We need to produce a derivation of the following:

`fib: Int => Int, n: Int ⊢ if n <= 1 then 1 else (fib(n - 1) + fib(n - 2)): Int`

i.e., given that `fib` inductively has type `Int => Int` and the parameter `n` has type `Int`, we need to prove that the body of the function has the ascribed type `Int`.

The derivation can be constructed by following the structure of the term on the right-hand side, the body. We set $\Gamma = \text{fib}: \text{Int} \Rightarrow \text{Int}, n: \text{Int}$ for brevity. The `n-2` branch is skipped due to space and being the same as the `n-1` branch.

$$\begin{array}{c}
 \frac{(n, \text{int}) \in \Gamma}{\Gamma \vdash n: \text{Int}} \quad \frac{1 \in \mathbb{N}}{\Gamma \vdash 1: \text{Int}} \quad \frac{1 \in \mathbb{N}}{\Gamma \vdash 1: \text{Int}} \quad \frac{(\text{fib}, \text{Int} \Rightarrow \text{Int}) \in \Gamma}{\Gamma \vdash \text{fib}: \text{Int} \Rightarrow \text{Int}} \quad \frac{\frac{(n, \text{int}) \in \Gamma}{\Gamma \vdash n: \text{Int}} \quad \frac{1 \in \mathbb{N}}{\Gamma \vdash 1: \text{Int}}}{\Gamma \vdash (n - 1): \text{Int}} \quad \frac{\dots}{\Gamma \vdash \text{fib}(n - 2): \text{Int}} \\
 \hline
 \Gamma \vdash \text{if } n \leq 1 \text{ then } 1 \text{ else } (\text{fib}(n - 1) + \text{fib}(n - 2)): \text{Int}
 \end{array}$$

□

Exercise 3 Consider the following term t :

$$t = 1 \Rightarrow \text{map}(1, x \Rightarrow \text{fst}(x)(\text{snd}(x)) + \text{snd}(x))$$

where `map` is a function with type $\forall \tau, \pi. \text{List}[\tau] \Rightarrow (\tau \Rightarrow \pi) \Rightarrow \text{List}[\pi]$.

1. Label and assign type variables to each subterm of t .
2. Generate the constraints on the type variables, assuming t is well-typed, to infer the type of t .
3. Solve the constraints via unification to deduce the type of t .

Solution

1. We can label the subterms in the following way:

$$t : \tau = 1 \Rightarrow \text{map}(1, x \Rightarrow \text{fst}(x)(\text{snd}(x)) + \text{snd}(x)) \quad (1)$$

$$t_1 : \tau_1 = \text{map}(1, x \Rightarrow \text{fst}(x)(\text{snd}(x)) + \text{snd}(x)) \quad (2)$$

$$t_2 : \tau_2 = x \Rightarrow \text{fst}(x)(\text{snd}(x)) + \text{snd}(x) \quad (3)$$

$$t_3 : \tau_3 = \text{fst}(x)(\text{snd}(x)) + \text{snd}(x) \quad (4)$$

$$t_4 : \tau_4 = \text{fst}(x)(\text{snd}(x)) \quad (5)$$

$$t_5 : \tau_5 = \text{snd}(x) \quad (6)$$

$$t_6 : \tau_6 = \text{fst}(x) \quad (7)$$

$$1 : \tau_7 = 1 \quad (8)$$

$$x : \tau_8 = x \quad (9)$$

$$\text{map} : \tau_9 = \text{map} \quad (10)$$

We can choose to separately label x , 1 , and map , but it does not make any difference to the result.

2. Inserting the type of map (thus removing τ_9), and adding constraints by looking at the top-level of each subterm, we can get the set of initial constraints, labelled by the subterm equation above they come from:

$$\tau = \tau_7 \Rightarrow \tau_1 \quad (1)$$

$$\tau_1 = \text{List}[\tau_3] \quad (2, 4)$$

$$\tau_7 = \text{List}[\tau_8] \quad (2, 9)$$

$$\tau_2 = \tau_8 \Rightarrow \tau_3 \quad (3)$$

$$\tau_3 = \text{int} \quad (4)$$

$$\tau_4 = \text{int} \quad (4)$$

$$\tau_5 = \text{int} \quad (4)$$

$$\tau_6 = \tau_5 \Rightarrow \tau_4 \quad (5)$$

$$\tau_8 = (\tau'_5, \tau_5) \quad (6)$$

$$\tau_8 = (\tau_6, \tau'_6) \quad (7)$$

for fresh type variables τ'_5 and τ'_6 arising from the rule for pairs.

3. The constraints can be solved step-by-step (major steps shown):

- (a) Eliminating known types (τ_3, τ_4, τ_5):

$$\tau = \tau_7 \Rightarrow \tau_1$$

$$\tau_1 = \text{List}[\text{int}]$$

$$\tau_7 = \text{List}[\tau_8]$$

$$\tau_2 = \tau_8 \Rightarrow \text{int}$$

$$\tau_6 = \text{int} \Rightarrow \text{int}$$

$$\tau_8 = (\tau'_5, \text{int})$$

$$\tau_8 = (\tau_6, \tau'_6)$$

(b) Eliminating τ_1, τ_6 :

$$\begin{aligned}\tau &= \tau_7 \Rightarrow \text{List}[\text{int}] \\ \tau_7 &= \text{List}[\tau_8] \\ \tau_2 &= \tau_8 \Rightarrow \text{int} \\ \tau_8 &= (\tau'_5, \text{int}) \\ \tau_8 &= (\text{int} \Rightarrow \text{int}, \tau'_6)\end{aligned}$$

(c) Eliminating τ_8 using either of its equations:

$$\begin{aligned}\tau &= \tau_7 \Rightarrow \text{List}[\text{int}] \\ \tau_7 &= \text{List}[(\tau'_5, \text{int})] \\ \tau_2 &= (\tau'_5, \text{int}) \Rightarrow \text{int} \\ (\tau'_5, \text{int}) &= (\text{int} \Rightarrow \text{int}, \tau'_6)\end{aligned}$$

(d) Performing unification of the pair type:

$$\begin{aligned}\tau &= \tau_7 \Rightarrow \text{List}[\text{int}] \\ \tau_7 &= \text{List}[(\tau'_5, \text{int})] \\ \tau_2 &= (\tau'_5, \text{int}) \Rightarrow \text{int} \\ \tau'_5 &= \text{int} \Rightarrow \text{int} \\ \text{int} &= \tau'_6\end{aligned}$$

(e) Eliminating τ'_5 and τ'_6 :

$$\begin{aligned}\tau &= \tau_7 \Rightarrow \text{List}[\text{int}] \\ \tau_7 &= \text{List}[(\text{int} \Rightarrow \text{int}, \text{int})] \\ \tau_2 &= (\text{int} \Rightarrow \text{int}, \text{int}) \Rightarrow \text{int}\end{aligned}$$

(f) Eliminating τ_2, τ_7 :

$$\tau = \text{List}[(\text{int} \Rightarrow \text{int}, \text{int})] \Rightarrow \text{List}[\text{int}]$$

(g) Finally, all type variables are assigned, as we eliminate τ :

$$\emptyset \text{ (no constraints left)}$$

The type of t as discovered by the unification process is:

$$\tau = \text{List}[(\text{int} \Rightarrow \text{int}, \text{int})] \Rightarrow \text{List}[\text{int}]$$

□

Exercise 4 Consider the following definition for a recursive function g :

```
def g(n, x) = if n <= 2 then (x, x) else (x, g(n - 1, x))
```

1. Evaluate $g(3, 1)$ and $g(4, 2)$ using the definition of g . Suggest a type for the function g based on your observations.
2. Label and assign type variables to the definition parameters, body, and its subterms.
3. Generate the constraints on the type variables, assuming the definition of g is well-typed.
4. Attempt to solve the generated constraints via unification. Argue how the result correlates to your observations from evaluating g .

Solution

1. $g(3, 1)$ evaluates to $(1, (1, 1))$ and $g(4, 2)$ evaluates to $(2, (2, (2, 2)))$. Notably, these two come from disjoint types. This suggests that the function g is not well-typed.
2. We can label the parameters, subterms, and assign a type to the function:

$$g : \tau \tag{1}$$

$$n : \tau_n \tag{2}$$

$$x : \tau_x \tag{3}$$

$$body : \tau_1 = \text{if } n \leq 2 \text{ then } (x, x) \text{ else } (x, g(n - 1, x)) \tag{4}$$

$$t_1 : \tau_2 = n \leq 2 \tag{5}$$

$$t_2 : \tau_3 = (x, x) \tag{6}$$

$$t_3 : \tau_4 = (x, g(n - 1, x)) \tag{7}$$

$$t_4 : \tau_5 = g(n - 1, x) \tag{8}$$

$$t_5 : \tau_6 = n - 1 \tag{9}$$

3. We can generate the constraints by looking at the top-level of each subterm equation:

$$\tau = \tau_n \Rightarrow \tau_x \Rightarrow \tau_1 \tag{1, def}$$

$$\tau_1 = \tau_3 \tag{4}$$

$$\tau_1 = \tau_4 \tag{4}$$

$$\tau_2 = \text{bool} \tag{4}$$

$$\tau_n = \text{int} \tag{5}$$

$$\tau_3 = (\tau_x, \tau_x) \tag{6}$$

$$\tau_4 = (\tau_x, \tau_5) \tag{6}$$

$$\tau_5 = \tau_1 \tag{7, def}$$

$$\tau_6 = \text{int} \tag{9}$$

4. The constraints can be solved (eliminating τ_4, τ_5) to reach a set of constraints containing the recursive constraint $\tau_1 = (\tau_x, \tau_1)$. There is no type τ_1 (the output type of $\mathbf{g}!$) satisfying this.

This matches our previous observation where \mathbf{g} produced two different sized tuples as its output.

□